



ECOSEAL REPAIR SYSTEM

TECHNICAL DATA SHEET

PRODUCT CODE

- 3625, 3386, 3624

DESCRIPTION

External injection system designed for sealing leaking joints on gas, process industry and water pipe systems.

FEATURES

- Cures without an anaerobic environment or without the need for an additional activator.
- Supplied in a 400ml side by side cartridge, with static mixer, which can be resealed for multiple applications.
- Unique formulation enables easy onsite in all weather conditions.
- Suitable for application on a wide range of pipe sizes and types, including valves.
- System that seals live gas pipes up to 2bar pressure, without stemming the leak or dropping the pressure.
- Approved to Gas Industry Standard (GIS) L25, that has a 50-year life standard.
- End cured product is tough yet flexible, allowing excellent pipe movement
- Suitable for single person application

CURING

- Within 6 minutes

COLOUR

- Red – Thick Viscosity
- Green – Low Viscosity
- Yellow – Ultra Low Viscosity

PERFORMANCE

- Permanently seals leaking joints or valves.
- Bonds to cast iron and steel
- Approved to a 50-year life standard
- Allows pipe movement.
- Excellent performance in harsh environments

STORAGE AND SHELF LIFE

- 18 Months in unopened container stored in temperate conditions

DIRECTIONS FOR USE

- Refer to instruction leaflet.

PRECAUTIONARY INFORMATION

Refer to the product label and material safety data sheet for health and safety information before using this product. All products should be used in accordance with your own COSHH Assessments.

FURTHER INFORMATION

For further information on the safe and efficient use of this or any other product in our range or to arrange training, contact our team on +44 (0) 1332 835001 or see our website for details.