



## PE REPAIR SYSTEM

# TECHNICAL DATA SHEET

### PRODUCT CODE

- 1624, 1605, 1604

### DESCRIPTION

External repair system designed for sealing leaks on Polyethylene (PE) and PVC distribution gas, process industry and water pipe systems.

### FEATURES

- Supplied in an easy to apply kit form. The unique formulation enables easy onsite in all weather conditions.
- System that seals live gas pipes up to 750 millibar pressure, without stemming the leak or dropping the pressure.
- Approved to Gas Industry Standard (GIS) LC8 and DVGW 30658 50-year gas standards.
- Application is by hand, no special tools required.
- End cured product is tough yet flexible, allowing subsequent pipe movement because of seasonal ground changes.
- Suitable for application on a wide range of pipe sizes and types, including pipes with misalignment.
- Suitable for single person application

### CURING

- Cured Pad

### COLOUR

- Light Green

### PERFORMANCE

- Excellent adhesion to plastic, PE80, PE100 and PVC
- Seals damage hole up to 40mm diameter
- Excellent performance in harsh environments
- Resistant to sunlight, mould, mildew & fungus

### STORAGE AND SHELF LIFE

- 12 Months in unopened container stored in temperate conditions

### DIRECTIONS FOR USE

- Refer to instruction leaflet.

### PRECAUTIONARY INFORMATION

Refer to the product label and material safety data sheet for health and safety information before using this product. All products should be used in accordance with your own COSHH Assessments.

### FURTHER INFORMATION

For further information on the safe and efficient use of this or any other product in our range or to arrange training, contact our team on +44 (0) 1332 835001 or see our website for details.